Service	Interval	Туре	Quantity
Replace Hydraulic Return Filter	*250 hours		
Replace Two Hydraulic Charge Filters	*250 hours		
Replace Engine Oil and Filters	*400 hours	AGCO® Powerlube Multiguard® Engine Oil (See engine manual for viscosity recommendations)	11.5 L (12.2 quarts) WR9X40, WR9X60 25.5 L (27 quarts) WR9X70
Replace Final Drive Planetary Oil	*500 hours	AGCO® Gearlube 710 M1103 Transmission Oil SAE 90  AGCO® Gearlube Gear/Axle Oil 715 M1134 SAE 80W-90	- 1.6 L (3.3 pints) each
Replace Pump Drive Gearcase Oil	*500 hours	Castrol Syntec Full Synthetic Gear Oil SAE 75W-90	3 L (3.2 quarts
Replace Fuel Filters	500 hours		
Replace Hydraulic Oil	2,000 hours or annually	AGCO <sup>®</sup> AW MV ISO 46 hydraulic oil <sup>[1]</sup>	99.6 L (26.3 gallons)  Tank capacity  123 L (32.5 gallons)  Total system capacity
Cooling System	Two years	AGCO® Antifreeze & Summer Coolant	30 L (8 U. S. gallons) WR9X40, WR9X60 34 L (9 U. S. gallons) WR9X70
	*Initial at 50 Hours		
[1] AGCO® Permatran® 821XL or equivilant can be used, but can cause hard engine starting in cold conditions.			